

Night Moves Ultraloc® Pattern

Product Specifications

| | | |
|-----------------------------|-----------------------------------|-------------------------|
| Collection Name | pdQ | |
| Style Number | I0129 | |
| Product Type | Broadloom | |
| Construction | Pattern Loop | |
| Fiber Type | Eco Solution Q® SD Nylon | |
| Dye Method | 80% Solution Dyed / 20% Yarn Dyed | |
| | English | Metric |
| Gauge | 5/64 inch | 50.4 per 10cm |
| Stitches Per Inch | 10 per inch | 41 per 10cm |
| Tufted Pile Height | 3/32" low - 6/32" high | 2.38mm - 4.76mm |
| Tufted Yarn Weight | 26.0 oz/yd2 | 881.6 gms/sqm |
| Finished Pile Thickness | 0.109 inches | 2.77 mm |
| Total Thickness | 0.287 inches | 7.29 mm |
| Product Size | 12.00 feet | 3.66 m |
| Average Density | 8587 per cu.yd. | 15.94 kilotex |
| Installation Pattern Repeat | 3/4"W X 1 3/4"L | 19.05 mm w x 44.45 mm l |
| Protective Treatments | SSP® Shaw Soil Protection | |
| Primary Backing | Woven Synthetic | |
| Secondary Backing | Ultraloc® | |

Performance Specifications

| | |
|--------------------------|--|
| Traffic Class | Heavy (TARR) |
| Antimicrobial Assessment | Passes (AATCC-174) (When installed using Shaw 1036 adhesive) |
| Methenamine Pill Test | Passes (DOCF-1-70) |
| Radiant Panel | Class I (ASTM E-648) |
| NBS Smoke | Less than 450 (ASTM-E-662) |
| Electrostatic Propensity | Less than 3.5 kV (AATCC-134) |
| CRI Green Label Plus | GLP2271 |
| ADA Compliance | This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes. |

Warranty Information

Broadloom Lifetime Commercial Limited Warranty

Installation Methods

Direct Glue



Environmental Specifications

Recyclability 100% recyclable

Materials

Ingredients

does not contain PVC, phthalates, or PBD/PBDE

Recycled Content

| | |
|---|-----------------|
| Total Recycled Content (by weight) | 10 % |
| Pre-Consumer | 10 % |
| Post-Consumer | 0 % |
| Bio-Based/Rapidly Renewable Content (By Weight) | 0 % |
| Packaging | 100% Recyclable |
| Country of Origin (manufacturer) | USA |

Meets or exceeds all local and national regulations in country of manufacture.

Manufactured in an ISO9001 & ISO14001 certified facility or equivalent.

Recycled content is calculated using system allocation, mass balance, and direct insertion.

The actual recycled content in this product will likely vary. For more information email info@patcraft.com.

Third Party Certifications

| | |
|----------------------|----------------|
| NSF 140 | Gold Certified |
| CRI Green Label Plus | GLP2271 |
| USGBC LEED | contributes |

Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate specification changes without notice. This carpet is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another carpet design is also strictly prohibited. Visit patcraft.com/testing for more information.