

Technique ClassicBac®

Product Specifications

Collection Name	Strategy	
Style Number	I0248	
Product Type	Broadloom	
Construction	Pattern Loop	
Fiber Type	Eco Solution Q® SD Nylon	
Dye Method	100% Solution Dyed	
	<b>English</b>	<b>Metric</b>
Gauge	1/10 inch	39.4 per 10cm
Stitches Per Inch	10 per inch	41 per 10cm
Tufted Pile Height	5/32"	3.97mm
Tufted Yarn Weight	24.0 oz/yd2	813.8 gms/sqm
Finished Pile Thickness	0.129 inches	3.28 mm
Total Thickness	0.277 inches	7.04 mm
Product Size	12.00 feet	3.66 m
Average Density	6698 per cu.yd.	11.44 kilotex
Installation Pattern Repeat	1/2" W x 1 1/4" L	12.70 mm w x 31.75 mm l
Protective Treatments	SSP® Shaw Soil Protection	
Primary Backing	Woven Synthetic	
Secondary Backing	ClassicBac®	

Performance Specifications

Traffic Class	Heavy (TARR)
Antimicrobial Assessment	Passes (AATCC-174) (When installed using Shaw 1036 adhesive)
Methenamine Pill Test	Passes (DOCF-1-70)
Radiant Panel	Class I (ASTM E-648)
NBS Smoke	Less than 450 (ASTM-E-662)
Electrostatic Propensity	Less than 3.5 kV (AATCC-134)
CRI Green Label Plus	GLP8472
ADA Compliance	This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes.

Warranty Information

Broadloom 10-year Commercial Limited Warranty

Installation Methods

Direct Glue

transforming performance.



## Environmental Specifications

---

Recyclability 100% recyclable

## Materials

---

### Ingredients

does not contain PVC, phthalates, or PBD/PBDE

### Recycled Content

Total Recycled Content (by weight)	10 %
Pre-Consumer	10 %
Post-Consumer	0 %
Bio-Based/Rapidly Renewable Content (By Weight)	0 %
Packaging	100% Recyclable
Country of Origin (manufacturer)	USA

Meets or exceeds all local and national regulations in country of manufacture.

Manufactured in an ISO9001 & ISO14001 certified facility or equivalent.

Recycled content is calculated using system allocation, mass balance, and direct insertion.

The actual recycled content in this product will likely vary. For more information email [info@patcraft.com](mailto:info@patcraft.com).

## Third Party Certifications

---

NSF 140	gold certified
CRI Green Label Plus	GLP8472
USGBC LEED	contributes

Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate specification changes without notice. This carpet is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another carpet design is also strictly prohibited. Visit [patcraft.com/testing](http://patcraft.com/testing) for more information.