

## Formwork

### Product Specifications

|                             |                           |                |
|-----------------------------|---------------------------|----------------|
| Collection Name             | Infrastructure            |                |
| Style Number                | I0518                     |                |
| Product Type                | Modular                   |                |
| Construction                | Multi-Level Pattern Loop  |                |
| Fiber Type                  | Eco Solution Q® Nylon     |                |
| Dye Method                  | 100% solution dyed        |                |
|                             | <b>English</b>            | <b>Metric</b>  |
| Gauge                       | 1/10 inch                 | 39.4 per 10cm  |
| Stitches Per Inch           | 10 per inch               | 39 per 10cm    |
| Tufted Pile Height          | 6/32"                     | 4.76mm         |
| Tufted Yarn Weight          | 16.0 oz/yd2               | 542.5 gms/sqm  |
| Finished Pile Thickness     | 0.070 inches              | 1.78 mm        |
| Total Thickness             | 0.218 inches              | 5.54 mm        |
| Product Size                | 24.0 X 24.0 inches        | 61.0 x 61.0 cm |
| Average Density             | 8229 per cu.yd.           | 9.07 kilotex   |
| Square Yards per Box        | 5.33                      |                |
| Installation Pattern Repeat | none                      |                |
| Protective Treatments       | SSP® Shaw Soil Protection |                |
| Primary Backing             | Synthetic                 |                |
| Secondary Backing           | EcoWorx® Tile             |                |
| GSA Approved Product        | Yes                       |                |




### Performance Specifications

|                          |  |
|--------------------------|--|
| Traffic Class            | Heavy (TARR)   |
| Antimicrobial Assessment | Passes (AATCC-174)<br>(When installed using Shaw 5036 adhesive)  |
| Methenamine Pill Test    | Passes (DOCF-1-70)   |
| Radiant Panel            | Class I (ASTM E-648)   |
| NBS Smoke                | Less than 450 (ASTM-E-662)   |
| Electrostatic Propensity | Less than 3.5 kV (AATCC-134)   |
| CRI Green Label Plus     | Certified GLP 9968   |
| ADA Compliance           | This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes. |

### Warranty Information

Carpet Tile Lifetime Commercial Limited Warranty

### Installation Methods



transforming performance.



## Environmental Specifications

---

Recyclability 100% recyclable

## Materials

---

### Ingredients

does not contain PVC, phthalates, or PBD/PBDE

### Recycled Content

|   |                 |
|---|-----------------|
| Total Recycled Content (by weight)              | 46 %            |
| Pre-Consumer                                    | 46 %            |
| Post-Consumer                                   | 0 %             |
| Bio-Based/Rapidly Renewable Content (By Weight) | 0 %             |
| Packaging                                       | 100% Recyclable |
| Country of Origin (manufacturer)                | USA             |

Meets or exceeds all local and national regulations in country of manufacture.

Manufactured in an ISO9001 & ISO14001 certified facility or equivalent.

Recycled content is calculated using system allocation, mass balance, and direct insertion.

The actual recycled content in this product will likely vary. For more information email [info@patcraft.com](mailto:info@patcraft.com).

## Third Party Certifications

---

|                                     |                    |
|-------------------------------------|--------------------|
| MBDC Cradle to Cradle               | Silver Certified   |
| NSF 140                             | gold certified     |
| CRI Green Label Plus                | Certified GLP 9968 |
| USGBC LEED                          | contributes        |
| Building Research Establishment     | certified          |
| Good Environmental Choice Australia | certified          |
| Singapore Green Label               | Certified 039-003  |

Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate specification changes without notice. This carpet is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another carpet design is also strictly prohibited. Visit [patcraft.com/testing](http://patcraft.com/testing) for more information.